

P39092

DESCRIPTION

PLASMA DISPLAY PANEL

5 This application is a U.S. National Phase application of PCT
International Application PCT/JP2005/008648

TECHNICAL FIELD

 The present invention relates to a plasma display panel for use in a
10 display device or the like.

BACKGROUND ART

 The plasma display panel (hereafter referred to as PDP) consists
basically of a front substrate and a rear substrate.

15 The front substrate comprises: a glass substrate; display electrodes
including stripe-like transparent electrodes and bus electrodes formed on a
principal surface of the glass substrate; a dielectric layer covering the
display electrodes to act as a capacitor; and a protective layer composed of
MgO formed on the dielectric layer.

20 The glass substrate adopts a glass substrate produced by float process,
a glass manufacturing technology easy for large-sizing and excellent in
flattening. The display electrodes include transparent electrodes provided
by the TFT (thin film transistor) processing, on which predetermined
patterns are formed using a paste including Ag to obtain a sufficient
25 electrical conductivity before sintering it to form the bus electrodes. The
dielectric glass layer is formed by sintering a dielectric paste coated so as to
cover the display electrodes having the transparent electrodes and bus

P39092

electrodes. Finally, a protective layer composed of MgO is formed on the dielectric layer by the TFT processing.

The rear substrate comprises: a glass substrate; stripe-like address electrodes formed on a principal surface of the glass substrate; a dielectric
 5 layer covering the address electrodes; ribs formed on the dielectric layer; and phosphor layers provided between the ribs internally to emit red, green and blue light respectively.

The front substrate and rear substrate are sealed hermetically so that principal surface sides provided with the electrodes face each other, and the
 10 discharge spaces divided by the ribs are filled with discharge gas such as Ne-Xe gas mixture at a pressure of ranging from 400 Torr to 600 Torr.

The PDP allows the display electrodes to discharge by applying image signal voltage selectively, exciting each phosphor layer to emit red, green and blue light by the ultra-violet ray generated in the discharge to perform
 15 colored image displaying. The examples are disclosed in "*General Information on Plasma Display*" by H. Uchiike & S. Mikoshiba, (Tokyo: Kogyo Chosakai Publishing Co., Ltd. May 1, 1997), p. 79 to 80.

In recent years, however, expectations for TV sets with high-resolution and multi-gradation and that consume less power, including
 20 high- definition TVs, are increasing rapidly. A fully equipped 42-inch high-definition TV set expected recently has 1920×1125 pixels with a very small cell pitch of 0.15×0.48 mm. The problem of decrease in the brightness and luminous efficiency would become apparently in such a high-resolution PDP.

25 Measures therefore such as to increase Xe concentration in the discharge gas or to use double-cross shaped ribs for the PDP has been tried. However, increased Xe concentration in the discharge gas or introduction of

P39092

the double-cross shaped ribs for the PDP could cause a large increase in a drive voltage and an unstable address discharge, thereby causing a problem of obtaining a high picture quality.

The present invention aims at providing a PDP capable of displaying
5 with high brightness and of realizing a stable driving on the low drive voltage.

DISCLOSURE OF THE INVENTION

To accomplish the above purposes the PDP of the present invention
10 has discharge spaces filled with the discharge gas between two substrates positioned facing each other with a gap, wherein the discharge gas is composed of at least one chosen from among helium (He), neon (Ne) and argon (Ar), xenon (Xe) and hydrogen (H₂), in which Xe concentration is not lower than 5%.

15 The configuration, the discharge gas including Xe of the concentration of not lower than 5% added with H₂ content, can provide the PDP capable of displaying with high brightness and of realizing a stable driving in the low drive voltage.

20 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a cross-sectional perspective view showing the main structure of the PDP used in the exemplary embodiment of the present invention.

FIG. 2 illustrates a cross-sectional view taken along the line A - A in
25 FIG. 1.

FIG. 3 illustrates the relationship between H₂ concentration in the discharge gas and the discharge voltage of the PDP used in the exemplary

P39092

embodiment of the present invention.

FIG. 4 illustrates the relationship between Xe concentration in the discharge gas and the maximum discharge voltage drop for the PDP.

FIG. 5 illustrates a view showing brightness variations on H₂ concentration in the discharge gas for the PDP.

FIG. 6 illustrates the relationship between Xe concentration in the discharge gas and the maximum increase rate of brightness for the PDP.

FIG. 7 illustrates the relationship between Xe concentration in the discharge gas and the maximum increase rate of luminous efficiency for the PDP.

DETAILED DESCRIPTIONS OF THE INVENTION

Now, the PDP used in the exemplary embodiment of the present invention is described with reference to the drawings.

FIG. 1 illustrates a cross-sectional perspective view showing the main portion of the PDP used in the exemplary embodiment of the present invention. FIG. 2 illustrates a cross-sectional view taken along the line A - A in FIG. 1. The PDP comprises front substrate 1 and rear substrate 2 positioned facing each other so that discharge spaces are formed as shown in FIG. 1.

Front substrate 1 is described first.

Front glass substrate 3 has display electrodes 6 including stripe-like scan electrodes 4 and sustain electrodes 5 arranged on a surface facing rear substrate 2 so as to form surface discharge gaps sandwiched between the both electrodes. That is, display electrode 6 comprises a pair of scan electrode 4 and sustain electrode 5 arranged in parallel. Scan electrode 4 and sustain electrode 5 comprise: transparent electrodes 4a and 5a

P39092

composed of transparent electrical conductive materials such as indium tin oxide (ITO) or tin dioxide (SnO_2); and bus electrodes 4b and 5b, having a narrower width and a higher electrical conductivity than transparent electrodes 4a and 5a, formed on transparent electrodes 4a and 5a. Bus electrodes 4b and 5b are formed of for instance Ag thick film (thickness: 2 to 10 μm), Al thin film (thickness: 0.1 to 1 μm) or Cr/Cu/Cr multi-layered thin film (thickness: 0.1 to 1 μm).

Dielectric layer 7 composed of dielectric glass materials having a glass composition of for instance $\text{PbO-SiO}_2\text{-B}_2\text{O}_3\text{-ZnO-BaO}$ series is formed on front glass substrate 3 provided with display electrodes 6 so as to cover display electrodes 6, and protective layer 8 is formed multi-layered on the entire surface of dielectric layer 7. MgO-based thin film thus formed is to act as protective layer 8.

Rear substrate 2 is described next.

Rear glass substrate 9 has a plurality of address electrodes 10 formed arranged in stripe-shape on the surface facing front substrate 1. Dielectric layer 11 is formed additionally so as to cover address electrodes 10. Stripe-like ribs 12 for instance are disposed on dielectric layer 11 so as to be arranged between address electrodes 10. Stripe-like grooves surrounded by ribs 12 and dielectric layer 11 are provided with phosphor layers 13: red phosphor layers 13R to emit red light, green phosphor layers 13G to emit green light and blue phosphor layers 13B to emit blue light.

Front substrate 1 and rear substrate 2 thus formed are positioned facing each other so that display electrodes 6 cross address electrodes 10 to form discharge spaces 14 surrounded by stripe-like grooves formed by ribs 12 and respective color phosphor layers 13R, 13G or 13B, and protective layer 8. Front substrate 1 and rear substrate 2 are hermetically sealed in

P39092

the outer periphery using sealing glasses, and subsequently discharge spaces 14 are filled with discharge gas to complete the PDP. Therefore, areas where display electrodes 6 cross address electrodes 10 work as discharge cells to perform image displaying. Discharge spaces 14 are filled
5 with the discharge gas at a pressure of the order of 400 Torr to 600 Torr.

The PDP generates ultra-violet rays with a short wave length (wave length: approximately 147 nm) in a gas discharge occurring in the discharge cells, and excites respective color phosphor layers 13R, 13G and 13B by the ultra-violet ray to perform image displaying.

10 In the exemplary embodiment of the present invention, discharge spaces 14 are filled with the discharge gas composed of at least one chosen from among helium (He), neon (Ne) and argon (Ar); xenon (Xe) and hydrogen (H₂), in which Xe concentration is not lower than 5%. Increased Xe concentration in the discharge gas enables the PDP to realize a
15 displaying with high-brightness. However, a higher Xe concentration increases the discharge voltage, causing circuit parts and PDP structure to need measures to withstand a higher voltage, thereby causing increase in power consumption and parts cost eventually.

The PDP used in the exemplary embodiment of the present invention
20 employs the discharge gas with an increased Xe concentration and with additional H₂ content, enabling the prevention of the discharge voltage from increasing to perform a stable operation while realizing the display with a high brightness.

Now, sample PDPs have been manufactured to check characteristics
25 of the PDP used in the exemplary embodiment of the present invention. The test samples include Xe concentration of 5%, 15% and 30% respectively, with H₂ content varying in concentration for each Xe concentration. The

P39092

sample PDPs have been finished manufactured with discharge cells 14 filled with the discharge gas, including Ne as a buffer gas, at a pressure of 66.7 kPa (500 Torr). The discharge voltage is measured in each sample subsequently.

5 FIG. 3 shows the relationship between H_2 content in the discharge gas and the discharge voltage. The least amount of H_2 content added to the discharge gas effects a decrease in the discharge voltage in every Xe concentration as shown in FIG. 3. On the contrary, if H_2 concentration reaches of the order of a few percent, the discharge voltage proves to show
10 an increase inversely. Namely, it proves that H_2 concentration of not higher than 0.1% or preferably not larger than 500 ppm can decrease the discharge voltage more than the case without any H_2 content.

 Additionally, an H_2 concentration ranging from 50 ppm to 500 ppm proves to have approximately the same effects on a decrease in the
15 discharge voltage, showing approximately a constant value over the range. That is, if H_2 content to the discharge gas is controlled in the concentration range, it may be preferable to practical manufacturing of the PDP because the effects on decrease in the discharge voltage may be stable if the concentration of H_2 content fluctuates slightly.

20 FIG. 4 illustrates the relationship between Xe concentration in the discharge gas and the maximum discharge voltage drop, showing differences between the discharge voltage in the case without any H_2 content and the discharge voltage minimized by adding H_2 content in each Xe concentration.

 FIG. 4 proves that H_2 content can decrease the discharge voltage in
25 every Xe concentration, and that the maximum drop of the discharge voltage amounts to ranging approximately 15 V to 18 V. Also it proves that the higher Xe concentration, the larger the voltage lowering effect.

P39092

FIG. 5 illustrates a view showing variations of display brightness against H₂ concentration in the discharge gas. Relative brightness on the same discharge voltage is shown, taking the brightness in the case without any H₂ content as a normal of 1 in each Xe concentration. FIG. 5 proves
 5 that the brightness shows the maximal value with H₂ concentration of not higher than 100 ppm in every Xe concentration.

FIG. 6 illustrates the relationship between Xe concentration in the discharge gas and the maximum increase rate of the brightness. The brightness maximized by adding H₂ content in each Xe concentration is
 10 shown in increase rate, taking the brightness in the case without any H₂ content as a normal of 1. FIG. 6 proves that the higher the Xe concentration, the larger the increase rate of brightness by adding H₂ content.

The aforementioned results prove that addition of H₂ content of not
 15 higher than 100 ppm can decrease the discharge voltage and can realize the display with high-brightness.

FIG. 7 illustrates the relationship between Xe concentration in the discharge gas and the maximum increase rate of the luminous efficiency. As shown in FIG. 7, though the luminous efficiency does not increase
 20 significantly in Xe concentration of 5%, but a big increase is shown with Xe concentration of not lower than 5%, and further increase with the increase in Xe concentration. Namely, it proves that an increase in the luminous efficiency can be achieved effectively by adding H₂ content with Xe concentration of not lower than 5%.

25 The luminous efficiency described above is determined by the following formula:

$$\text{Luminous efficiency } \eta \text{ (lm/W)} =$$

P39092

$$\pi \times \text{brightness (cd/m}^2\text{)} \times \text{operating area (m}^2\text{)} /$$

$$(\text{power for lighting} - \text{power for non-lighting})$$

From the above, H₂ content should not be higher than 0.1 %, preferably not higher than 500 ppm, or more preferably not higher than 100 ppm to achieve a higher luminous efficiency when Xe concentration is not lower than 5%. That can realize approximately 20 V decrease in the discharge voltage and of the order of 20% further increase in the luminous efficiency at the same time compared with the case without any H₂ content.

The voltage lowering measures enable the PDP to decrease the discharge voltage and to reduce withstand voltage levels required for circuit parts or structure of the PDP, resulting in a cost reduction effectively.

Additionally, the voltage lowering measures also enable the PDP to operate on a lower drive voltage and to improve the luminous efficiency further if the drive voltage is optimized.

The above description results from the PDP with protective layer 8 composed of magnesium oxide (MgO) used as the main component. Considering the collision probability between the gases, the aforementioned H₂ concentration of the order of ppm is negligibly small from the collision theory, while resulting in significantly. Generally, hydrogen (H₂) decreases the electron temperature, causing the discharge voltage to increase. From the above, therefore, the results of the present invention can be considered as follows: Hydrogen (H₂) is considered to act on magnesium oxide (MgO) composing protective layer 8 forming a portion of internal surface of discharge space 14, allowing magnesium oxide (MgO) acting as a cathode to increase the electron emissivity. It is considered, therefore, that the materials of protective layer 8 should preferably include magnesium oxide (MgO) as the main component.

P39092

Although a flat-reflection type PDP is used in the above description, the present invention can be adopted for facing-discharge type PDP or tube-array type PDP as well, and particularly the improvement of luminous efficiency can be a more effective measure to reduce the power consumption

5 in large-sized PDPs such as 60-inch and up.

INDUSTRIAL APPLICABILITY

As aforementioned, the present invention can reduce the drive voltage of the PDP and can perform displaying with high brightness by

10 introducing a discharge gas including Xe of the concentration of not lower than 5% added with H₂ content, which would be useful for a plasma display apparatus for use in a wall-hung TV or large-sized screen monitor.